

APEX VOC Speciate up to 20 VOC gases

Apex VOC is a series of three portable, autonomous, cloud-enabled VOC analyzers designed to operate in both indoor and outdoor environments. The analyzer's real-time measurement capabilities enable timely actionable insights and eliminate operational and service costs associated with labor, processing time, and laboratory testing.

Apex VOC was developed with ease-of-use and manageability in mind.

Cloud-based IoT connectivity allows each analyzer or a cluster of analyzers to be managed remotely through a single screen management console.


Connectivity includes Wi-Fi and optional cellular (4G/LTE). This capability enables analyzers to be deployed at local and remote locations and managed from anywhere in the world. The management application tool tracks VOC data over time, monitors analyzer health, identifies analyzer location, and provides customers with the ability to program the measurement frequency.



Technical specs

	2240	2240EB	2260
	2240	ZZ40LD	2200
Measuring Component	Benzene, toluene, m-xylene and o-xylene (BTX)	Benzene, Ethylene dichloride (EDC)	Benzene, toluene, m-xylene and o- xylene (BTX), others by request
Limit of Detection			
Benzene	<1ppb	<1 ppb	<1 ppb
Toluene	<1ppb	n/a	<1 ppb
m-Xylene	<1ppb	n/a	<1 ppb
0-Xylene	<1ppb	n/a	<1 ppb
Ethylene dichloride (EDC)	n/a	<1 ppb	

2240/2260



Characteristics

VOC Detector Omniscent MEMS

Other Sensors Temperature, relative humidity,

flowmeter

Pump Flow Rate 0.5 - 15 sccm

Communication Wi-Fi LTE via ext modem
Sensor Cloud Secure IoT cloud infrastructure

Sampling Time 2-40 minutes (User programmable)

Embedded Data Storage 32 GB


Environmental

Relative Humidity 0 - 100%

Ambient Temperatures 0 - 40°C (32-104°F)

Apex Instruments 204 Technology Park Way Fuquay Varina, North Carolina 27526 (919) 557-7300 www.apexambientair.com

22240EB



Power

Power Supply Input 100-120/200-240 VAC Power Supply Output V1: +12V/7A; V2: +24V/4A

Fail Safe 4 Amps

Power Consumption 50W Max, 4W Idle, Typical 25W

Field Installation

Dimensions H: 35.26 cm (13.87 in.)

W: 20cm (8 in.), D: 14.61cm (5.75 in.)

Weight 7.3 kg (16 lbs.)

Housing Material Aluminum

