

# Apex Instruments Heated Sample Line Legend

HS  L  -  /  /  /  -

**Heater Control**  
 BLANK = Unregulated  
 R = Self-Regulating

**Cover**  
 B = Silicone Coated Tetraglass  
 F = Flexible Polyamide Conduit

**Sample Line Tubing**  
 (Create Part Number from Largest to Smallest Tubing Size)  
 4 = 1/4" O.D. (.047" Wall/PFA) 4H = 1/4" O.D. (.062" Wall/PFA)  
 6 = 3/8" O.D. (.062" Wall/PFA)  
 8 = 1/2" O.D. (.062" Wall/PFA)  
 10 = 5/8" O.D. (.062" Wall/PFA)  
 \*NOTE: Multiple Line Combinations Available  
 EXAMPLES: 4/4, 6/4, 8/4, 8/6, 8/8

**Sample Line Termination**  
 BLANK = 1 Foot of Raw Tubing  
 BS = Bulkhead Tube Stub (Only available on 4, 6 or 6/4 lines)  
 BU = Bulkhead Union (Only available on 4, 6 or 6/4 lines)

**Length (in Feet)**

**Power Pass Through (120V = 5-15 240V = C14V) BLANK**  
 = None  
 P# = Number of Power Lines [1-3]: P1, P2, P3

**TC Pass Through**  
 BLANK = None  
 T# = Number of TCs[1-6]: T1, T2, T3, T4, T5, T6

**Voltage/Power Plug**  
 BLANK = 120V- Uses 5-15 (UL 15 amps)  
 C14 = 120V (UL 15 amps)  
 C14V = 240V (UL 15 amps)  
 C20 = 120V (UL 20 amps)  
 C20V = 240V (UL 20 amps)  
 520 = 120V (UL 20 amps)  
 L520 = 120V (UL 20 amps/Locking)  
 620V = 240V (UL 20 amps)  
 L620V = 240V (UL 20 amps/Locking)

**Low Amperage**  
 BLANK = 30 Watts per Foot  
 LA = 24 Watts per foot-Only Available on 120V, 100 ft.